

constructive solutions

Number: UK9-151

# **DECLARATION OF PERFORMANCE**

In accordance with Annex III of Registration (EU) No. 305/2011
(Construction Product Regulation)
amended by Commission Delegated Regulation (EU) No 574/2014

1 Unique identification code of the product-type:

#### PROOFEX TOTAL, 2154020

2 Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:

#### Flexible plastic damp proof sheets

3 Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



Fosroc International Limited Drayton Manor Business Park Coleshill Road, Tamworth Staffordshire, B78 3XN, UK

4 Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):

### **Not Relevant**

5 System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V

#### System 2+

6a In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard

EN 13967:2012

The notified body

## Kiwa MPA Bautest GmbH 0799

6b In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued

## Not Relevant

Issue number: 6



# Fosroc<sup>®</sup> Proofex Total

constructive solutions

Number: UK9-151

## 7 Declared performance

| Essential Characteristics                         | Performance                     | Test Method  |
|---|---------------------------------|--------------|
| Durability water tightness after artifical ageing | Pass                            | EN 1296      |
| Durability water tightness against chemicals      | Pass                            | EN 1847      |
| Joint strength                                    | NPD                             | EN 12317-2   |
| Reaction to fire                                  | Class E                         | EN 13501-1   |
| Resistance to impact                              | 450mm                           | EN 12691     |
| Resistance to static load                         | 20kg load: Pass                 | EN 12730     |
| Resistance to tearing                             | MD: >270N, CMD: >330N           | EN 12310-1   |
| Tensile Properties                                | MD >500 N/50mm, CMD >380 N/50mm | EN 12311-2   |
| Watertightness                                    | Method A: Pass                  | EN 1928:2000 |

8 Appropriate Technical Documentation and/or Specific Technical Documentation:

## **Not Relevant**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

pe les

Signed for the manufacturer and in the name of the manufacturer by:

Jon Potter

**Technical Manager** 

Place and Date of Issue: 05/10/2021

Tamworth

Issue number: 6