



Er referens:

Vår referens: Morgan Larsson

Datum: Februari 2022

## TEKNISKT DATABLAD

### Celsa Flowstop

GTIN:	4251689510212
customs tariff number:	39169050
packing unit:	cart
sales quantity unit:	120 m
weight per:	cart = 18 kg
material:	TPE
colour:	red
surface:	smooth
hardness:	40 - 50 Shore A DIN 53505-A
elongation:	up to 300% DIN 53571
increase in volume:	up to 600%, in neutral water (ph7) up to 100 %, in salt water
test certificate/ approval:	Test report (abP) MFPA Leipzig Nr.: P-SAC 02 / 5.1 / 13-515  Eropean Technical Assessment ETA-18/0304 of 18 June 2018  Test report acid resistance MPA Braunschweig (1200/442/15d)-Pan of 28.10.2015
suitable for zones with frequently varying water levels:	yes
corresponds to:	Utility class A for the wear classes 1 and 2 in accordance with the WU guideline



resistant to:

e.g.

- Diluted acids and alkalis
- Salt water
- Methane gas
- Radon
- Liquid manure and slurry
- Fermentation mash and biogas
- Concrete alkalinity
- Mineral oils
- Fuels (Petrol, Diesel, Kerosine)

packaging:	6 rolls à 20 m 120 m per carton 36 cartons par palette
thermal scope of application:	approx. -30°C up to +60°C
waterpressuretightness:	up to max. 8 bar ( 80m water column )
storage:	Store in undamaged and unopened original packaging in a dry place out of direct sunlight.
disposal:	Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.
Dimensions:	20 x 5 mm