



Er referens:

Vår referens: Erik Sandell

Datum: Februari 2023

## TEKNISKT DATABLAD

### Celsa Master Fogbleck

GTIN:	4251689511394
customs tariff number:	73269098
packing unit:	crate
sales quantity unit:	100 m
weight per:	crate = 155 kg
material:	St 37, galvanised
colour:	black
surface:	stiff, sticky
length of joint sheet metal:	2.50 m
height of joint sheet metal:	160 mm
thickness of joint sheet metal:	Approx. 0.6 mm
thickness of special coating:	Approx. 0.8 mm
total thickness:	Approx. 2.1 mm
test certificate / approvals:	Test report PB 5.1/16-502 MFPA Leipzig
suitable for zones with frequently varying water levels :	yes
corresponds to:	Utility class A for the wear classes 1 and 2 in accordance with the WU guideline



packaging: wooden crate (255 x 30 x 25 cm)  
40 strips  
55 fixing clips

12 crates per pallet

---

thermal scope of application: - 10°C to + 50°C

---

waterpressuretightness: Up to max. 3 bar (30 m water column)

---

storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight.

---

disposal: Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.

---