



Er referens:

Vår referens: Morgan Larsson

Datum: Februari 2022

## TEKNISKT DATABLAD

### Celsa Masterstop Bentonit

GTIN:	4251689510014
customs tariff number:	40027000
packing unit:	cart
sales quantity unit:	30 m
weight per:	cart = 22.8 kg
material:	sodium bentonite
colour:	black
surface:	smooth
consistency:	malleable
profile:	25x20 mm
weight:	22,80 kg / carton
volume increase:	up to 240%, in normal water (pH 7)  up to 120%, in liquids that are highly aggressive to concrete  up to 220%, in alkaline liquids
test certificate / approvals:	ETA – 16 / 0735
:	
	Investigation report, MFPA Leipzig No.: PB 5.1 / 12-299
suitable for zones with frequently varying water levels:	yes
corresponds to: :	Utility class A for the wear classes 1 and 2 in accordance with the WU guideline



resistances:

E.g.

- Alkalis in general
- Urea
- Liquid manure and slurry
- Biogas
- Radon
- De-icing salt
- Substances obtained by means of fermentation
- Substances obtained by means of composting
- Waste water in water treatment plants

Further resistances are available on request

packaging:	size: 25 x 20 mm 30 m per carton 6 rolls of 5 m each 36 cartons per pallet
thermal scope of application:	approx. . -30°C to +90°C
waterpressuretightness:	tested up to max. 5 bar (50 m watercolumn) AbP approval up to max. 2 bar (20 m watercolumn)
storage:	Store in undamaged and unopened original packaging in a dry place out of direct sunlight.
disposal:	Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.